


## ANTENNAS | XPOL-6-10M

# XPOL-6-10M

1710 - 2700 MHZ LTE MIMO ANTENNA



- Very high constant gain
- Futureproof wideband LTE antenna and Wi-Fi operational frequencies
- Backwards compatible with 3G and 2G technologies
- Two antennas in one enclosure for optimal LTE performance
- Increased connectivity stability

### Product Overview

This unique antenna provides a unique solution with a constant level of very high gain for 4G, 3G and 2G networks. It is a unique wall- or pole-mountable, dual polarised, full LTE band antenna. Incorporating two separately fed ultra wideband elements in a single housing, the antenna is equipped to provide client-side MiMo and diversity support for the networks of today and tomorrow. This is a cost effective solution for enhancing signal reception. The XPOL-6-10M antenna increases signal reliability, ensures higher data throughput for users and provides a stable, high quality connection.

This improves subscriber user experience and secures client retention. It is ideal for any application using the GSM network (LTE/HSPA/3G/EDGE/GPRS).

### Features

- Wideband - covers wide frequency band
- Wall or pole mountable
- Lightweight
- Two antennas in one enclosure


### Application areas


- Urban and rural areas
- Poor data signal reception (indoor or outdoor)
- Slow data transmission connection
- Unstable connection
- Increase system transmission reliability
- LTE fringe areas (close to an LTE area, but just out of reach)
- Network operator flexibility - as the antennas is wideband, a new antenna is not needed per network operator - works on most networks



## Frequency bands


The XPOL-6-10M is a wide-band antenna that works from 1710 - 2700 MHz

 Indicates the bands on which this antenna works



## Antenna Performance Plots


**VSWR:**



**Voltage Standing Wave Ratio (VSWR)**

VSWR is a measure of how efficiently radio-frequency power is transmitted from a power source, through a transmission line, into a load. In an ideal system, 100% of the energy is transmitted which corresponds to a VSWR of 1:1. The XPOL-6-10M delivers superior performance across all bands with a VSWR of 2:1 or better.

**Gain: (excluding cable loss)**



**Gain\* in dBi**

11dBi is the peak gain across all bands from 1710 - 2700 MHz


Gain @ 1710 - 2700 MHz:

11 dBi




\*Antenna gain measured with polarisation aligned standard antenna

## Radiation Patterns

Azimuth:



Elevation:



## Electrical Specifications

Frequency Bands:	1710 - 2700 MHz
Gain (Max):	11 dBi
VSWR:	< 2:1
Feed Power Handling:	10 W
Input impedance:	50 Ohm (nominal)
Polarisation:	+ 45° and - 45°
Port to Port Isolation:	>15dB
MIMO decorrelation:	< 0.3
Cable loss:	0.35dB/m @900 MHz 0.53dB/m @ 2000 MHz 0.6dB/m @2500 MHz
DC Short:	Yes

## Mechanical Specifications

Product Dimensions (L x W x D):	300 mm x 145 mm x 57 mm
Packaged Dimensions:	360 mm x 160 mm x 115 mm
Weight:	1,35 kg
Packaged Weight:	1,60 kg
Radome Material:	ABS (Halogen Free)
Radome Colour:	Pantone - Cool Gray (1C) RAL 7047

## Environmental Specifications

Wind Survival:	<120km/h
Temperature Range (Operating):	-40°C to +70°C
Environmental Conditions:	Outdoor/Indoor
Operating Relative Humidity:	Up to 98%
Storage Humidity:	5% to 95% - non condensing
Storage Temperature:	-40°C to +70°C

## Product Box Contents

Antenna:	A-XPOL-0006-10M
Mounting Bracket:	Wall or pole mount
Cable Length:	10m
Cable Type:	Twin siamese HDF 195
Connector:	2X SMA (M) Gold plated)
<i>The cables and connectors are factory mounted to the antenna</i>	



A-XPOL-0006-10M



## Ordering Information

Commercial name:	XPOL-6-10M
Order Product Code:	A-XPOL-0006-10M
EAN number:	6009693810129

## Additional Accessories Available

Extension Cables:	Up to 10m HDF 195
Various connectors available	
Installation poles and brackets available	

## Certification Approvals and Standards

Flammability rating:	UL 94-V0 EN 13823
Water Ingress Protection Ratio/Standard:	IP 65 (NEMA 4X)
Impact resistance:	IK 08
Salt Spray:	MIL-STD 810F/ASTM B117
Product Safety:	Complies with UL, CE, EN, CSA and IEC standards

For more detailed information and availability in your region,  
visit our web site: [www.poynting.tech](http://www.poynting.tech)



## Contact Poynting

### Poynting Antennas (Pty) Ltd - Head Office

Unit 4, N1 Industrial Park  
Landmarks Avenue,  
Samrand, 0157  
South Africa

**Phone:** +27 (0) 12 657 0050  
**E-mail:** [sales@poynting.co.za](mailto:sales@poynting.co.za)

### Poynting Europe

Regus Business Center Neue Messe Riem  
Kronstadter Straße 4  
81677 München  
Germany

**Phone:** +49 89 208026538  
**E-mail:** [sales-europe@poynting.tech](mailto:sales-europe@poynting.tech)

### XPOL-6-10M

©2015 Poynting Antennas (Pty) Ltd. All rights reserved  
Product Specifications may change without prior notice  
Revised: September 2015

Regulatory Compliance: RoHS 2011/65/EU Compliant | ISO 9001:2008  
Document version: TS-XPOL-0006-10M\_v00  
[www.poynting.tech](http://www.poynting.tech)