

CABLES | A-CAB-092

CAB-092

5M TWIN SIAMESE CABLE HDF195 SMA(M)- TO SMA(F)



Electrical Specifications

| | |
|----------------------|---------------------|
| Capacitance: | 24.3pF/m |
| Conductor: | Bare Copper Wire |
| Shield Coverage: | 88% |
| Minimum Bend Radius: | 12.7mm |
| Input Impedance | 50 Ohm (nominal) |
| Cable loss: | 0.25dB/m @ 450 MHz |
| | 0.35dB/m @900 MHz |
| | 0.53dB/m @ 2000 MHz |
| | 0.6dB/m @2500 MHz |

Mechanical Specifications

| | |
|---------------------------------|-----------------|
| Product Dimensions (L x W x D): | 2 x 5m x 4.95mm |
| Packaged Dimensions: | 300mm x 160mm |
| Weight: | 0.175 kg |
| Packaged Weight: | 0.185 kg |
| Conductor diameter: | 0.95mm |
| Dielectric diameter: | 2.84mm |
| Inner conductor diameter: | 2.96mm |
| Outer conductor diameter: | 3.54mm |
| Jacket diameter: | 4.95mm |

Environmental Specifications

| | |
|--------------------------------|-----------------------------|
| Temperature Range (Operating): | - 20° to + 70°Environmental |
| Conditions: | Outdoor/Indoor |
| Operating Relative Humidity: | Up to 98% |
| Storage Humidity: | 5% to 95% - non condensing |
| Storage Temperature: | -- 20° to + 70° |

Product Box Contents

| | |
|---------------|--------------------|
| Product: | A-CAB-092 |
| Cable Length: | 5m |
| Cable Type: | HDF195 |
| Connector: | SMA (f) and SMA(m) |



Ordering Information

| | |
|---------------------|-----------|
| Commercial name: | CAB-092 |
| Order Product Code: | A-CAB-092 |

Certification Approvals and Standards

| | |
|----------------------|---|
| Flammability rating: | UL:1581 |
| Impact resistance: | IK 05 |
| Product Safety: | Complies with UL, CE, EN, CSA and IEC standards |

Additional Accessories Available

| | |
|------------------------------|-------------------|
| Extension Cables: | Up to 10m HDF 195 |
| Various connectors available | |



For more detailed information and availability in your region, visit our web site: www.poynting.tech

Contact Poynting

Poynting Antennas (Pty) Ltd - Head Office

Unit 4, N1 Industrial Park
Landmarks Avenue,
Samrand, 0157
South Africa

Phone: +27 (0) 12 657 0050

E-mail: sales@poynting.co.za

Poynting Europe

Regus Business Center Neue Messe Riem
Kronstadter Straße 4
81677 München
Germany

Phone: +49 89 208026538

E-mail: sales-europe@poynting.tech

CAB-092

©2015 Poynting Antennas (Pty) Ltd. All rights reserved.
Product Specifications may change without prior notice
Revised: September 2015

Regulatory Compliance: RoHS 2011/65/EU Compliant | ISO 9001:2008
Document version: TS-CAB-092
www.poynting.tech